

Hip Adductor & Abductor-HM1819

- 1: Main Frame Gauge "Flat Oval Tube 50*100*2.5mm; Shroud Frame Rectangular Tube 50*110*2.0mm;
Motion Arms Flat Oval Tube 40*80*2.0mm; Motion Arms Round Tube Φ 50*2.5mm"
- 2: Wire Spec. Dia 5.6mm
- 3: Cushion Material: High strength sponge, artificial PVC leather
- 4: Guiding Bar Round 20*2.0mm Stainless Steel Bar
- 5: Shroud Cover Integrated iron guard plate makes the equipment safe, beautiful and seamless
- 6: Handle Made of TPV material, soft, non-slip and durable
- 7: Adjusting Position Pulling bar adjustment structure
- 8: Weight Stack Steel plate thickness : 18mm; Better impact and wear resistance; Standard configuration: 80kgx1 group, 5kg/piece
- 9: Pulleys High Strength Nylon Pulleys, which have passed the over 100,000 times non-stop fatigue tests
- 10: Accessories High strength bolts and locknuts, which can meet National Standard Grade 8.8, are better in strength and rust resistance.
- 11: Size/ N.W. Size: 1547*1310*1601mm (L*W*H)
- 12: Size/ N.W.
- 13: Manual Chinese Manual English Manual
- 14: Muscles Trained Exercise the thigh adductor and abductor.